

Gen			

Order No. 0638120000
Part designation SAKG 54/35 II

Version Special terminal, special connections, 240 mm²,

Screw connection, KrG, Medium yellow, TS 35

EAN 4008190068646

Qty. 5 pc(s).

Product notes

Note, technical data

Conductor connection with cable lugs according to

Medium vellow

Stud terminal

DIN 46234 and DIN 46235, from 70 .. 240 mm²

Additional technical data Colour of insulating material

Octobri of insulating material	Wediam yellow
Connection direction	on side
End plate required	Yes
Explosion-tested version "Ex e"	No
Installation advice	TS 35
Insulating material	KrG
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	2
Open sides	Open
Operating temperature range	- 60 °C, + 130 °C
Product family	SAK Series
Type of connection	Screwed
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	5VA

CSA rating data

Version

Voltage (CSA) 600 V
CSA current 600 A
Min. cross-section (CSA) kcmil 300
Max. cross-section (CSA) kcmil 500

Conductors for clamping (rated connection)

Clamping range, min. 10 mm²
Clamping range, max. 240 mm²

Type of connection Screw connection

2nd type of connection screwed Connection direction on side



Conductors for clamping (rated connection)		
No. of connections	1	
Clamping screw	M 16	
Tightening torque range	2560 Nm	
AWG conductor size, min.	kcmil 300	
AWG conductor size, max.	kcmil 500	
AWG conductor size, min.	150 mm²	
AWG conductor size, max.	253.35 mm²	
Dimoneione		

Dimensions

Width	54 mm
Height of lowest version	60.5 mm
Length	122 mm
TS 32 offset	43.5 mm
TS 35 offset	61 mm

Rating data

Rated cross-section	240 mm ²
Rated voltage	1,000 V
Rated impulse voltage	8 kV
Rated current	415 A
Standards	IEC 60947-7-1
Current with max. conductor	415 A
Pollution severity	3

UL rating data

Voltage (UL)	600 V
Current (UL)	380 A
Min. cross-section (UL)	kcmil 300
Max. cross-section (UL)	kcmil 500

Approvals

Approvals institutes



Classifications		
ETIM 2.0	EC000897	
ETIM 3.0	EC000897	
eClass 4.1	27-14-11-31	
eClass 5.0	27-14-11-31	
eClass 5.1	27-14-11-31	

Similar products



0638220000	SAKG 54/35 II/GW	Special terminal, special connections, 240 mm ² , Screw connection,
		KrG, Medium yellow, TS 35

